



仕様

種類	形状・サイズ	タイプ	目詰り防止加工あり																	目詰り防止加工なし																		
			40	60	80	100	120	150	180	240	280	320	360	400	500	600	800	1000	1200	1500	2000																	
ジ ス ク	○ 50Φ	HNAD	○	○	○																																	
		HRAD																																				
	○ 100Φ	HNAD	○	○	○																																	
		HRAD																																				
	● 115Φ	HNBD	○	○	○																																	
		HRBD					○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○				
	○ 125Φ	HNAD	○	○	○																																	
		HRAD																																				
● 125Φ	HNWD	○	○	○																																		
	HRWD																																					
○ 150Φ	HNAD	○	○	○																																		
	HRAD																																					
● 150Φ	HNOD	○	○	○																																		
	HROD																																					
シ ー ト	75×110	HNAS	○	○	○																																	
		HRAS																																				
	75×110	HNCS	○	○	○																																	
		HRCS																																				
	75×170	HNAS	○	○	○																																	
		HRAS																																				
	75×170	HNCS	○	○	○																																	
		HRCS																																				
	95×180	HNCS	○	○	○																																	
		HRCS																																				
	100×180	HNAS	○	○	○																																	
		HRAS																																				
100×180	HNJS	○	○	○																																		
	HRJS																																					
115×220	HNCS	○	○	○																																		
	HRCS																																					
115×225	HNBS	○	○	○																																		
	HRBS																																					
ロ ー ル	75×15m	HNAR	○	○	○																																	
		HRAR																																				
	100×15m	HNAR	○	○	○																																	
		HRAR																																				
	115×15m	HNAR	○	○	○																																	
		HRAR																																				

用途

- 自動車補修研磨作業
- 各種車両における塗膜研磨
- 金属焼付塗装研磨作業
- 建物塗装・インテリア工事での研磨作業
- 木工・家具メーカーでの各種研磨作業

特長

- 番手の取り換えがワンタッチ。
- キレが抜群。
- 目づまりが少なく長持ち（ロングライフ）。
- ペーパー目が出にくい。
- 耐水性があり、水との併用も可能。
- パットが痛まない——パット面がいつも平滑。

梱包仕様

形状	サイズ	粒度	入数(枚)	
			大箱	小箱
ジスク	125Φ・150Φ	40~120	500	50
		150~600	1000	50
シート	95×180	40~600	500	50
	100×180			
	115×220			
	75×170			
	75×240			
	95×400			
	100×300			
100×400				
	75×110	40~400	1000	100

形状	サイズ	入数(巻)		
		大箱	小箱(包)	1
ロ ー ル	75×15M	10	10	1
	100×15M	5	10	
	115×15M	5	5	

化粧箱の色

HN系	みどり色(グリーン)
HR系	あい色(ディープブルー)
HL系	ぎん色(シルバー)

●ご用命はぜひ下記代理店へ……